

Automated Backup

Starting from Lucy 4.6 has been added the ability to create and configure automatic backups. The administrator can configure automatic backups that are stored in local directory

/opt/phishing/files/db-backups

The Automated Backup Settings is available under the Settings menu:

The screenshot shows the Lucy Security AG interface. The top navigation bar includes 'Settings' and a user profile icon. The main content area is titled 'Automated Backup' and contains several configuration options: 'Backup Target' (DB), 'Backup Frequency' (Monthly), 'Backup Time' (01:30), and 'Backup Days' (1). A 'Save' button is visible. The 'Settings' menu is open, displaying a list of settings categories. 'Automated Backup Settings' is highlighted with a red box. Other settings categories include Templates, Benchmark Sectors, Domains, Dynamic DNS, Adapt Authoring Toolkit, Recipients, Clients, End Users, Administrative Users, Reputation Levels, Incident Settings, Firewall, Web Proxy, Mail Settings, SMTP Servers, SSL Settings, SMS Settings, LDAP Settings, API Whitelist, SSO Configuration, and Automated Response Detection.

Automated Backup Settings

- **Backup Target**

You can select which components of the system should be backed up. Click "Deselect All" to turn off the backup task:

[Home](#) / Automated Backup

Automated Backup Settings

Backup Target

DB, Files, Rainloop, Config, (▼)

Select All

Deselect All

DB



Files



Rainloop



Config



Code



Save

Backup Frequency

Backup Time

Backup Days

1. Database - creates an SQL dump of the whole Lucy database;
2. Files - creates an archived copy of the folder “/opt/phishing/files” that contain campaigns data, templates and etc. (it is recommended to use with Database);
3. Rainloop - creates an archived copy of settings and all folders of the Mail Manager;
4. Config - creates an archived copy of Lucy's configuration files (web server, mail server and etc.);
5. Code - creates an archived copy of Lucy's source code and executables.

• Backup Frequency

The frequency of running the backup tasks can be set to various intervals:

1. Daily
2. Weekly
3. Monthly
4. Yearly

[Home](#) / Automated Backup

Automated Backup Settings

Backup Target

DB, Files, Rainloop, Config, (▼)

Backup Frequency

Monthly ▼

Backup Time

Daily

Weekly

Monthly

Yearly

Backup Days

Save

- **Backup Time**

You can choose a convenient time to run the backup task. Depending on the components selected for backup, the task may take a long time, so we recommend that you schedule the time when the server load is minimal (usually at night).

- **Backup Days**

Specify the days when the backup task should be run. Days of week or month: 1-7 for weekly, 1-31 for monthly. Days of the year: 1-12 (month numbers); 1-31 (days of the month) for yearly.

- Example for weekly: 1,3,5,7
- Example for monthly: 1, 15, 25
- Example for yearly: 1,3,5,7;1,15

[Home](#) / Automated Backup

Automated Backup Settings

Backup Target

DB, Files, Rainloop, Config, (▼)

Backup Frequency

Monthly ▼

Backup Time

00:10

**Backup Days**

1,15,25

**Save**

From:

<https://wiki.lucysecurity.com/> - **LUCY**

Permanent link:

https://wiki.lucysecurity.com/doku.php?id=automated_backupLast update: **2019/07/25 12:49**